

Specifications

Model	R-10YPM	R-15YPM	R-20YPM	R-30YPM	R-40YPM	R-50YPM	R-60YPM	
Air Displacement @ Pressure (M ³ /min @ MPa/Bar)	1.08/0.7/7	1.65/0.7/7	2.3/0.7/7	3.6/0.7/7.0	5.1/0.7/7	6.2/0.7/7.0	7.2/0.7/7	
	0.98/0.8/8	1.58/0.8/8	2.1/0.8/8	3.4/0.8/8.0	5.0/0.8/8	6.0/0.8/8.0	7.0/0.8/8	
	0.86/1.0/10	1.40/1.0/10	1.9/1.0/10	3.1/1.0/10	4.7/1.0/10	5.7/1.0/10	6.4/1.0/10	
Air Displacement @ Pressure (CFM @ PSI)	38/102	58/102	81/102	127/102	180/102	219/102	254/102	
	35/116	56/116	74/116	120/116	177/116	212/116	247/116	
	30/145	50/145	67/145	109/145	166/145	201/145	226/145	
Volume of Lubricant (L)	5	10	10	12	22	22	23	
Noise Level dB(A)	68±2	70±2					74±2	
Compression Stage	Single stage							
Drive method	Direct drive							
Power Supply	380V/50Hz (can be customized as per your voltage and frequency requirements)							
Power (KW/HP)	7.5/10	11/15	15/20	22/30	30/40	37/50	45/60	
Motor Protection Class	IP23							
Starting Mode	Variable frequency starting							
Dimensions	Length (mm)	720	940	940	1110	1340	1340	
	Width (mm)	600	680	680	830	950	950	
	Height (mm)	800	950	950	1120	1200	1220	
N.W.	kg	105	195	195	290	396	415	
Outlet Diameter (inch)	G ³ /4"			G1"		G1-1/2"		

Note: We reserve the right to make design improvements without prior notice. Product specifications are subject to change, and the final specifications may vary depending on the actual machine.