

Specifications

Model	Power (W/HP)	Tank Volume	Maximum Pressure (Bar/PSI)	Frequency (Hz)	Air Displacement		Speed (R.P.M)	N.W./G.W kg	Dimensions (cm)
		L			L / Min	CFM			
HR-1008	900/1.25	8	8/115	50	118	4.16	2850	15 / 16	51*22*50
				60	141	4.99	3400		
HR-1524KC	1100/1.50	24	8/115	50	155	5.46	2850	20 / 22	58*25*58
				60	185	6.5	3400		
HR-1524B	1100/1.50	24	8/115	50	138	4.88	2850	19/21	58*25*58
				60	165	5.82	3400		
HR -2024B	1500/2			50	206	7.28	2850	20/22	
				60	246	8.7	3400		
HR -2524B	1800/2.5			50	270	9.53	2850	22/24	
				60	323	11.4	3400		
HR -1550B	1100/1.5	50	8/115	50	138	4.88	2850	26.5/28.5	72*33*68
				60	165	5.82	3400		
HR -2050B	1500/2			50	206	7.28	2850	28/30	
				60	246	8.7	3400		
HR -2550B	1800/2.5			50	270	9.53	2850	32/34	
				60	323	11.4	3400		
HR -1524F	1100/1.5	24	8/115	50	138	4.88	2850	19 / 21	58*25*58
				60	165	5.82	3400		
HR -2024F	1500/2			50	206	7.28	2850	20 / 22	
				60	246	8.7	3400		
HR -2524F	1800/2.5			50	270	9.53	2850	22 / 124	
				60	323	11.4	3400		
HR -1550F	1100/1.5	50	8/115	50	138	4.88	2850	26.5/28.5	72*33*68
				60	165	5.82	3400		
HR -2050F	1500/2			50	206	7.28	2850	28/30	
				60	246	8.7	3400		
HR -2550F	1800/2.5			50	270	9.53	2850	32/34	
				60	323	11.4	3400		
HR -2016B	1500/2	16	8/115	50	206	7.28	2850	15/16	51*22*50
				60	246	8.7	3400		
HR -2516B	1800/2.5			50	270	9.53	2850		
				60	323	11.4	3400		
HR -2050FV	1500/2	50	8/115	50	206	7.28	2850	20/22	58*25*58
				60	246	8.7	3400		
HR -2550FV	1800/2.5			50	270	9.53	2850		
				60	323	1.4	3400		
HR -2024Q	1500/2	24	8/115	50	206	7.28	2850	20/22	58*25*58
		60		246	8.7	3400			
HR -2050MK	1500/2	50		50	206	7.28	2850	28/30	
		60		246	8.7	3400			
HR -3050	2200/3	50	8/115	50	412	14.55	2850	40/43	72*36*70

Note: We reserve the right to make design improvements without prior notice. Product specifications are subject to change, and the final specifications may vary depending on the actual machine.