

Specifications

Model		HA-015XF	HA-020XF	HA-026XF	HA-038XF	HA-070XF	HA-110XF	HA-150XF	HA-180XF	HA-220XF	HA-280XF
Delivery Air Flow (Nm ³ /min)		1.5	2.5	2.5	3.8	6.5	10.5	13.5	17.0	21.5	28.5
N.W. (kg)		92	120	120	175	310	430	522	580	720	1000
Inlet/Outlet Diameter (inch/mm)	NB	G1"	G1"	G1"	G1½"	G1½"	G2"	G2"	DN65	DN80	DN80
	DN	DN25	DN25	DN25	DN40	DN40	DN50	DN50	DN65	DN80	DN80
Desiccant (kg)		24	37	37	60	92	430	185	225	300	445
Dimensions (mm)	Length (mm)	580	630	630	570	610	680	680	720	980	1060
	Width (mm)	670	730	730	840	1020	1160	1160	1195	1280	1460
	Height (mm)	1695	1805	1805	1690	1710	1900	2200	2175	2310	2320
Notes	1. Working pressure: 0.5-1.0Mpa 2. Dew point temperature: -40°C 3. Inlet temperature: ≤45°C 4. Working method: twin towers work in turn continuously										

Model		HA-320XF	HA-380XF	HA-460XF	HA-550XF	HA-670XF	HA-750XF	HA-850XF	HA-950XF	HA-1100XF
Delivery Air Flow (Nm ³ /min)		32.0	37.0	45.0	55.0	65.0	75.0	85.0	95.0	110.0
N.W. (kg)		1100	1180	1420	1670	2000	2320	2550	2850	3000
Inlet/Outlet Diameter (mm)	NB	DN80	DN100	DN100	DN100	DN125	DN125	DN125	DN150	DN150
	DN	DN80	DN100	DN100	DN100	DN125	DN125	DN125	DN150	DN150
Desiccant (kg)		500	580	695	880	1040	1200	1210	1700	2200
Dimensions (mm)	Length (mm)	1060	1080	1160	1150	1240	1240	1350	1430	1430
	Width (mm)	1460	1580	1765	1825	2040	2136	2210	2330	2450
	Height (mm)	2510	2460	2550	2690	2820	2930	2970	3250	2980
Notes	1. Working pressure: 0.5-1.0Mpa 2. Dew point temperature: -40°C 3. Inlet temperature: ≤45°C 4. Working method: twin towers work in turn continuously									

Note: We reserve the right to make design improvements without prior notice. Product specifications are subject to change, and the final specifications may vary depending on the actual machine.