

Specifications

Model	FA-10	FA-15	FA-18	FA-20	FA-24	FA-28	FA-36	FA-50	FA-75	FA-100	FA-130	FA-170	FA-190	FA-250	FA-280	FA-410	
Port Size	Rc1/2"	Rc3/4"	Rc3/4"	Rc1"	Rc3/4"	Rc3/4"	Rc1"	Rc1"	Rc1-1/2"	Rc2"	Rc2-1/2"	Rc2"	Rc2-1/2"	Rc3"	Rc3"	Rc3"	
Flow Rate (m ³ /min)	I/S	16.7	25	30	33.3	40	46.7	60	83.3	125	166.7	216.7	283.3	316.7	416.7	466.7	683.3
	m ³ /min	1	1.5	1.8	2	2.4	2.8	3.6	5	7.5	10	13	17	19	25	28	41
	CFM	35.3	53	63.6	70.6	84.7	99	127.1	177	264.8	353.1	459	600.3	671	883	988.7	1448
QTY	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
Dimensions	W (mm)	96	96	96	96	96	138	138	138	138	174	174	174	174	220	220	220
	D (mm)	79	79	79	79	79	111	111	111	111	142	142	142	142	184	184	184
	H (mm)	261	261	295	261	295	403	403	503	503	736	736	1016	1016	793	793	1050
	A	29	29	29	29	29	37	37	37	37	58	58	58	58	74	74	74
	B	198	198	233	198	233	296	296	396	396	607	607	887	887	649	649	906
	C (space of the housing)	118	118	153	118	153	208	208	303	303	469	469	794	794	514	514	764

Model	FB-007	FB-015	FB-024	FB-035	FB-060	FB-090	FB-120	FB-150	FB-240	FB-240	FB-360	FB-450	
Flow Rate (m ³ /min)	0.7	1.5	2.4	3.5	6	9	12	15	24	30	36	45	
Inlet/Outlet Size (inch/mm)	G3/4"-1	G3/4"-1	G111/2"	G111/2"	G111/2"	G211/2"	G211/2"	G211/2"	DN80	DN80	DN100	DN100	
Max. Working Pressure (Bar/PSI)	16/232	16/232	16/232	16/232	16/232	16/232	16/232	16/232	12/174	12/174	12/174	12/174	
Dimensions	W (mm)	280	280	340	340	490	550	930	930	1400	1400	1420	1420
	D (mm)	230	230	275	275	420	445	825	825	1300	1300	1320	1320
	H (mm)	90	90	110	110	110	150	150	150	390	390	480	480
N.W. (kg)	1.2	1.2	2.2	2.2	2.7	11	16	16	40	40	55	60	
Filter Element Model	007X1	015X1	024X1	035X1	060X1	090X1	120X1	150X1	120X2	150X2	120X3	150X3	

Note: We reserve the right to make design improvements without prior notice. Product specifications are subject to change, and the final specifications may vary depending on the actual machine.

